



MIG svejsseslange - effektiv, hvor pladsen er trang

Model ML 150 TWIST

Standard modeller

LM nr.

4347000010	3 m	0,8	80197150
4347000481	4 m	0,8	80197151
4347000482	5 m	0,8	80197153
4347000483	3 m	1,0 Alu	80197156

Modeller med regulering

4347000468	3 m	0,8	80196150
4347000469	4 m	0,8	80196151
4347000470	3 m	1,0 Alu	80196155



Gasdyse

E-Cu


4347000351	53,5 mm	80140023*
------------	---------	-----------



4347000352	55 mm	80140500
------------	-------	----------



4347000350	60 mm	80140022
------------	-------	----------



Kontakttdyse


E-Cu

4347000340	Ø0,6 M6	Ø8x28 mm	80130201
4347000341	Ø0,8 M6	Ø8x28 mm	80130202*
4347000342	Ø1,0 M6	Ø8x28 mm	80130203
4347000343	Ø1,2 M6	Ø8x28 mm	80130204



Dysestok

4347000300	Standard	34 mm	80110020 *
------------	----------	-------	------------




Holdefjeder

4347000301			80110021
------------	--	--	----------



Stålliner

4347000404	Hvid	for 0,6-0,8 tråd	80160520
4347000405	Blå	for 0,8-1,0 tråd	80160521



4,4 m (bruges også til 3 m slanger)

* = Standard monteret ved levering

Alle modeller leveres med spring pin.