



Product data sheet

6GK1500-0EA02



PB BUS CONNECTOR WITH AXIAL CABLE OUTLET
F.INDUSTR. PC,
SIMATIC OP, OLM;
TRANSMISSION RATE 12 MBIT/S;
TERMINATING RESISTOR WITH SEPAR.
FUNCTION,
METAL HOUSING

[nicht versorgt: PMD_ABS675_001_000]

•

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

•

2

• for network components and terminal equipment

1

Design of the electrical connection / [nicht versorgt - FastConnect]

No

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width

15 mm

Height

57 mm

Depth

39 mm

Net weight

100 g

Permitted ambient conditions

Ambient temperature

• during operating	0 °C ... 60 °C
• during storage	-25 °C ... 80 °C
• during transport	-25 °C ... 80 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	75 %
Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• [nicht versorgt - PG-Anschlussbuchse]	No
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	No
letzte Änderung:	Nov 21, 2011