




SITOP PSE200U 10 A SELECTIVITY MODULE 4-
CHANNEL INPUT: 24 V DC;
OUTPUT: 24 V D/10 A PER EACH CHANNEL OUTPUT
CURRENT ADJUSTABLE 3-10

Technical specifications

Product	SITOP PSE200U
Power supply, type	Selectivity module, 4 x 10 A
Input	
Input	Controlled DC voltage
Supply voltage / for DC / rated value	24 V
Input voltage	
• at DC	22 V ... 30 V
Overvoltage resistance	35 V
Input current / at nominal level of the input voltage 24 V / nominal value	40 A
Output	
Output	controlled DC voltage
Output voltage	V _{in} - approx. 0.2 V
Total tolerance	In accordance with the supplying input voltage
Number of channels / secondary side	4
Output current / at 60 °C / per channel / rated value	10 A
Adjustable output current	3 A ... 10 A
Output voltage setting	via potentiometer
Product feature / Bridging of channels	No

Type of channel connection	Simultaneous connection of all channels after power up of the supply voltage > 20 V, delay time of 25 ms, 100 ms or adjustable "load optimised" via DIP switch for sequential connection
Efficiency	
Efficiency at Vout rated, Iout rated, approx.	99 %
Power loss at Vout rated, Iout rated, approx.	10 W
Switch-off characteristic per channel	
Overcurrent switch-off	Iout = 1.0 ... 1.3 x set value, switch-off after approx. 5 s
Current limitation	Iout = 1.3 x set value, switch-off not before typ. 100 ms
Immediate switch-off	Iout > set value and Vin < 20 V, switch-off after approx. 0.5 ms
Reset	Using keys for each channel
Remote reset	Non-isolated 24 V input (signal level "high" at > 15 V)
Protection and monitoring	
Device/Line protection	15 A internal fuse per channel (not accessible)
Status display	Three-color LED per channel: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
Signaling	Common signal contact (changeover contact, rating 0.1 A/24 V DC)
Safety	
Standard / for security	according to EN 60950-1 and EN 50178
Protection class	Class III
CE mark	Yes
Degree of protection (EN 60529)	IP20
UL/cUL (CSA) approval	UL-Recognized (UL 2367), File E328600; cURus (UL 508, CSA C22.2 No. 107.1), File E197259
Standard / for explosion protection	ATEX (EN 60079-0, -15)
EMC	
Emitted interference	EN 55022 Class B
Noise immunity	EN 61000-6-2
Operating data	
Ambient temperature	
• in operation	0 °C ... 60 °C
• Note	with natural convection
Ambient temperature	
• on transport	-40 °C ... 85 °C
• in storage	-40 °C ... 85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
Mechanics	
Connection technology	screw-type terminals
Design of the electrical connection	

• at the input • secondary side • for signaling contact • for auxiliary contact	+24 V: 2 screw terminals for 0.5 ... 10 mm ² ; 0 V: 2 screw terminals for 0.5 ... 4 mm ² Output 1 ... 4: 1 screw terminal each for 0.5 ... 4 mm ² 3 screw terminals for 0.5 ... 4 mm ² Remote reset: 1 screw terminal for 0.5 ... 4 mm ²
Width / of the housing	72 mm
Height / of the housing	80 mm
Depth / of the housing	72 mm
Installation width	72 mm
Mounting height	180 mm
Net weight	0.2 kg
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Mechanical accessories	Device identification label 20 mm × 7 mm, pastel-turquoise 3RT1900-1SB20



letzte Änderung:

Oct 31, 2011