

SIEMENS

Product data sheet

6GK1500-0FC10

PB FC RS 485 PLUG 180,
PB-PLUG WITH FASTCONNECT CONNECTOR AND
AXIAL CABLE- OUTLET F. INDUSTRY PC,
SIMATIC OP, OLM,
TRANSMISSION RATE: 12 MBIT/S,
TERMINATING RESISTOR WITH SERAR.
FUNCTION,
PLASTIC HOUSING

[nicht versorgt: PMD_ABS675_001_000]

-

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

-

2

- for network components and terminal equipment

1

Design of the electrical connection / [nicht versorgt -
FastConnect]

Yes

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

16 mm

Height

62 mm

Depth

34.5 mm

Net weight

40 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 °C ... 60 °C

-25 °C ... 80 °C

-25 °C ... 80 °C

Relative humidity / at 25 °C / without condensation /
during operating / maximum

75 %

Protection class IP

IP20

Product properties, functions, components / general

Product feature / [not supplied - silicon-free]

Yes

Composant produit

- [nicht versorgt - PG-Anschlussbuchse]

No

- décharge de traction

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity

Yes

- UL-registration

Yes

letzte Änderung:

Nov 21, 2011