

## LAVORAZIONE MATERIE PLASTICHE

S.p.A. - Capitale Sociale € 3.000.000 Via XXV Aprile, 16 - 21020 Daverio (Va) Tel. +(39) 0332 942111 / +(39) 0332 947373 - Fax +(39) 0332 949696 REA N. 100622 VA - N. Mecc. VA 000987 Reg. Impr. di Varese, PI/CF: IT 00212770127 www.merlett.it - merlett@merlett.it

## DECLARATION OF CONFORMITY

We hereby declare that the hoses:

## 912904.....00 VACUPRESS SUPERELASTIC

are made of two- layer plasticized PVC with embedded galvanized steel spiral and polyester yarn reinforcement.

Operating temperature - 25°C to + 60°C.

Strictly avoid contact of food with the heads and outer surface of the tube.

The hoses must be sterilized prior to use.

Use: Suction and delivery of aqueous liquid, acid and alcoholic up to 20% foods; oily and / or fatty foods excluded.

The hoses are suitable for contact with aqueous food, acid and alcohol (up to 20%) for which A, B and C simulants are provided, for a maximum of 2 hours repeated contact at the maximum temperature of 70°C.

In compliance

with the following EU legislation:

Directive EEC no. 1978/142

Regulation (EC) no. 1935/2004

Regulation (EC) no. 1895/2005 (epoxy derivatives)

Regulation (EC) no. 2023/2006 (GMP)

Regulation (EC) no. 10/2011 and subsequent amendments

and the following Italian legislation:

Ministerial Decree 21/03/1973 and subsequent amendments and changes; Presidential Decree 777/82 and subsequent amendments and changes.

The items mentioned above were manufactured exclusively with substances (monomers, pigments and additives) indicated in the positive lists of the above

legislation. The material contains substances subject to restrictions in the laws mentioned and are listed below:

Ref. No	CAS No.	SML (mg/kg)
26050	75-01-4	0.01
66905	872-50-4	
88640	8013-07-8	60
92200	6422-86-2	60
93440	13463-67-7	<u> </u>
(*)		25
	26050 66905 88640 92200 93440	26050 75-01-4 66905 872-50-4 88640 8013-07-8 92200 6422-86-2 93440 13463-67-7

(\*) Annex II reg. UE 10/2011.

## Test conditions:

Simulant:

Time and Temperature:

B: acetic acid at 3% in aqueous solution

2 hours at 70°C (repeated use)

C: ethanol at 20% in aqueous solution

2 hours at 70°C (repeated use)

The simulants and test conditions were chosen according to Regulation (EU) n. 10/2011 (annex III tab. 1 and annex V tab.3)

The overall migration limit, together with the other specific restrictions to which the monomers and/or additives present in the material may be subject, are respected in the above-mentioned conditions of use. This statement has been supported by analytical tests conducted in accordance with Regulation (EC) n. 10/2011 and Ministerial Decree 21/03/1973 or on the basis of calculations made by considering the content of the substances subject to migration limits. The calculations were made assuming that 1kg of food is in contact with 6 dm2 of the material.

Dual-use additives. In the hose there are the following substances regulated by Regulations (EC) N. 1333/2008 (food additives) and 1334/2008 (flavourings), and its amendments:

Titanium Dioxide: E 171

Sodium, Potassium And Calcium Salts Of Fatty Acids; E 470a

E 479b Thermally Oxidised Soya Bean Oil Interacted With Mono- And Diglycerides Of Fatty Acids;

Fatty Acids; E 570

According to experimental data and/or theoretical calculations such substances comply with the requirements of Article. 11 of Regulation (EU) No 10/.2011 paragraph 3, letters "a" and "b" of D.M. 21/03/1973.

This declaration will be updated in the event of changes in formulation of the material or if the legislative references are modified and updated so as to require a new check for compliance purposes.

Daverio, 22.01.2016

signature of General Manager

Mr. Marso TAMBORINI