

Rustfrit stål

Kompakttavler AE

Bredde (B) mm		Pk.	760	800	800	1000	1000	1000	Side
Højde (H) mm			760	1000	1200	1000	1200	1200	
Dybde (T) mm			300	300	300	300	300	300	
Montagepladebredde (F) mm			704	739	740	939	940	940	
Montagepladehøjde (G) mm			730	955	1155	955	1155	1155	
Best.nr. AE		1 stk.	1014.600	1016.600	1017.600	1018.600	1019.600	1019.500¹⁾	
Materiale	1.4301 (AISI 304)		■	■	■	■	■	–	
	1.4404 (AISI 316L)		–	–	–	–	–	■	
3-punkts låsesystem			–	–	■	–	■	■	
Låge(r)			1	1	1	2	2	2	
Vægt (kg)			42,5	52,9	61,5	71,0	76,0	76,0	
Kapslingsklasse	IP 66 efter EN 60 529, NEMA 4X er opfyldt					IP 55 efter EN 60 529, NEMA 12 er opfyldt			
Tilbehør									
Montageskiner til indvendig udbygning		4 stk.	2373.300	2373.300	2373.300	2373.300	2373.300	2373.300	647
Regntag	1.4301 (AISI 304)	1 stk.	2474.000	2475.000	2475.000	2363.000	2363.000	2363.000	619
Vægbeslag	1.4301 (AISI 304)	4 stk.	2433.000	2433.000	2433.000	2433.000	2433.000	–	627
	1.4404 (AISI 316L)	4 stk.	–	–	–	–	–	2433.500	627
Vægmontagevinkel	1.4301 (AISI 304)	4 stk.	2583.010	2583.010	2583.010	2583.010	2583.010	2583.010	628
Vridelås 1.4404 (AISI 316L)	Standard	1 stk.	2304.000	2304.000	–	2304.000	–	–	609
	Hygienic Design	1 stk.	2304.010	2304.010	–	2304.010	–	–	178
Alternative låsesystemer		Se side 602							

¹⁾ Låseindsats: trykstøbt zink



Rittal Japan

RITTAL K.K.
Sales HQ.
Shin-Yokohama AK Bldg 2F
3-23-3, Shin-Yokohama, Kohoku-ku
Kanagawa 222-0033
Phone: 0120-998-631 / +81 (45) 478-6801
Fax: 0120-998-632 / +81 (45) 478-6880
E-mail: contact@rittal.co.jp • www.rittal.co.jp