




Ground Rod Clamp, Rod to Conductor, Bronze – C58 (158160)



- For use with copper-bonded ground rods
- Parts that are UL Listed are suitable for direct burial in earth or concrete



Part Number	C58
Article Number	158160
Torque (TQ)	25 N-m Max
Material	Gunmetal
Ground Rod Diameter, Nominal	1/2" – 5/8"
Ground Rod Diameter, Actual (Ø)	12,5 – 15,0 mm
Conductor Size	70 mm² Stranded Max
Wrench Size	14 mm
Complies With	IEC® EN 62561-1
Certifications	Qualifoudre
Standard Packaging Quantity	5 pc
UPC	78285687143
EAN-13	8711893001358

IEC is a registered trademark of the International Electrotechnical Commission.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.