# Elpress mini

## - electro-hydraulic crimping tool 6 to 70 mm<sup>2</sup>





The Elpress mini tool PVL350 in a new sleek design with a high performance Li-Ion battery that streamlines your work with its improved battery capacity.

#### CHARACTERISTICS:

- Single-handed operation for easy control of all tool functions
- Slim fitting crimping head ideal for confined spaces
- High-performance 10.8 V Li-Ion battery with indication of charge status
- Opening, rotatable "flip-top" head for easy die change and good accessibility
- Easy and comfortable to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Extremely lightweight and rapid crimping process for maximum efficiency
- Automatic return of dies when crimping is completed

#### **TECHNICAL DATA PVL350:**

35 kN
6-70 mm <sup>2</sup>
about 3-4 s (dependent on material)
about 180 for 70 mm² Cu
10.8 V
1.5 Ah, Li-Ion
about 40 minutes.
1.6 kg
-10°C to +40°C
330 x 85 x 60 mm

### **Elpress MINI – crimping dies**

Application		Area	Dies	
CUT-connector		6-16 mm²	MB4016	
		KR/KRD, KS/KSD	KR/KRF, KS/KSF	KRT/KST
Hexagonal 4-10 mm <sup>2</sup>		MB4016	MB4016	-
Hexagonal 10 mm <sup>2</sup>		MB8	MB8	MB7
÷	16 mm²	MB8	MB9	MB8,5
	25 mm²	MB9	MB11	MB10
	35 mm²	MB11	MB13	MB12
	50 mm²	MB12	MB14,5	MB14
	70 mm²	MB14	MB17	MB16
	95 mm²	MB17		
C-connectors		12-26 mm² (C6-10)	MBC5	
		30-50 mm² (C16-25)	MBC6	

**Elpress AB** • P.O. Box 186, SE-872 24 KRAMFORS, Sweden Tel: +46 (0)612-71 71 00 | Fax: +(0)46 612-71 71 51 E-mail: sales@elpress.se | www.elpress.net

