

QT-FIT 5/8 2X18...39

QUICKTRONIC FIT 5/8 | ECG for FL and CFL, not dimmable



Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I
- Modernization of existing systems

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50...60 Hz
- Lamp start with optimum filament preheating
- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

Technical data


Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
DC voltage	198...264 V
Operating frequency	40...50 kHz

Light technical data

Starting time	2.0 s
---------------	-------

Dimensions & weight



Product line drawing

Length	280.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	270.0 mm
Product weight	183.00 g

Temperatures

Ambient temperature range	-15...+50 °C
---------------------------	--------------

Capabilities

Dimmable	No
Suitable for fixtures with prot. class	I
End of lamp life safety shutdown	EOL T.2

Product datasheet

Certificates & standards

Approval marks – approval	CE / VDE / ENEC 10 / VDE-EMC
EEI – Energy Label	A2

Download Data

File	
	Product Family Datasheet Familiendatenblatt QT-FIT 5_8
	Certificates ENEC QT-FIT 5_8
	Certificates EMC QT-FIT 5_8
	Certificates CE Declaration QT-FIT 5_8

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

Lamp-ECG combination (System)

Product name	Lamp group	Luminous flux at 35 °C	Ambient temperature range [PIM]	Number of lighting outlets	Nominal current	Nominal wattage	Nominal wattage + Power loss	Luminous flux at 25 °C
QT-FIT 5/8 2x18-39	HO 24 W CONSTANT	1900 lm	-15...+50 °C	2				
	HO 24 W	1750 lm	-15...+50 °C	2	0.24 A	53 W	53.00 W	
	HO 39 W CONSTANT	3400 lm	-15...+50 °C	2				
	HO 39 W	3100 lm	-15...+50 °C	2	0.36 A	80 W	80.00 W	
	L 16 W ES	1100 lm	-15...+50 °C	2				
	L 18 W XT	1350 lm	-15...+50 °C	2				
	L 18 W XXT	1350 lm	-15...+50 °C	2		32 W	32.00 W	
	L 18 W	1350 lm	-15...+50 °C	2	0.17 A	32 W	39.00 W	
	L 30 W		+15...+50 °C	2	0.27 A	24 W	63.00 W	3000 lm
	L 36 W XT	3200 lm	-15...+50 °C	2		32 W	32.00 W	
	L 36 W XXT	3200 lm	-15...+50 °C	2		32 W	32.00 W	
	L 36 W	3200 lm	-15...+50 °C	2	0.31 A	32 W	32.00 W	

Lamp group	Product name	EAN
HO 24 W CONSTANT	HO 24 W/830 CONSTANT	-
	HO 24 W/840 CONSTANT	-
	HO 24 W/865 CONSTANT	-

Lamp group	Product name	EAN
HO 24 W	HO 24 W/827	-

Product datasheet

Lamp group	Product name	EAN
	HO 24 W/830	-
	HO 24 W/835	-
	HO 24 W/840	-
	HO 24 W/865	-
	HO 24 W/880	-

Lamp group	Product name	EAN
HO 39 W CONSTANT	HO 39 W/830 CONSTANT	-
	HO 39 W/840 CONSTANT	-
	HO 39 W/865 CONSTANT	-

Lamp group	Product name	EAN
HO 39 W	HO 39 W/827	-
	HO 39 W/830	-
	HO 39 W/840	-
	HO 39 W/865	-
	HO 39 W/880	-

Lamp group	Product name	EAN
L 16 W ES	L 16 W/830 ES	-
	L 16 W/840 ES	-

Lamp group	Product name	EAN
L 18 W XT	L 18W/830 XT	-

Product datasheet

Lamp group	Product name	EAN
	L 18W/840 XT	-
	L 18W/865 XT	-

Lamp group	Product name	EAN
L 18 W XXT	L 18W/830 XXT	-
	L 18W/840 XXT	-
	L 18W/865 XXT	-

Lamp group	Product name	EAN
L 18 W	L 18W/827	-
	L 18W/830	-
	L 18W/835	-
	L 18W/840	-
	L 18W/865	-
	L 18W/880	-

Lamp group	Product name	EAN
L 30 W	L 30W/827	-
	L 30W/830	-
	L 30W/840	-
	L 30W/865	-
	L 30W/880 SKYWHITE	-

Product datasheet

Lamp group	Product name	EAN
L 36 W XT	L 36W/830 XT	-
	L 36W/840 XT	-
	L 36W/865 XT	-

Lamp group	Product name	EAN
L 36 W XXT	L 36W/830 XXT	-
	L 36W/840 XXT	-
	L 36W/865 XXT	-

Lamp group	Product name	EAN
L 36 W	L 36 W/830-1	-
	L 36W/827	-
	L 36W/827-1	-
	L 36W/830	-
	L 36W/835	-
	L 36W/840	-
	L 36W/840-1	-
	L 36W/865	-
	L 36W/880	-