OUNEVA
OUNEVA GROUP

PRODUCT CARD

Product data

Product code	**VC04-0004**	STK-code	**5202433**	EAN-code	**6410052024338**
Product name	Insulated Universal connector 1xAl/Cu 16-120mm²				
Wires	1xAl/Cu 16-120mm²				

Technical data

Nominal current	Cu	**280**	A
	Al	**230**	A
Nominal voltage		**690**	V
Max. Current (US)	Cu	**-**	A
	Al	**-**	A
Max. Voltage (US)		**-**	V
Number of pole		**1**	pcs
Max. Cross section		**120**	mm²
Tightening torque	16-35 mm²	**12**	Nm
	50-120 mm²	**25**	Nm
	-	**-**	Nm
	-	**-**	Nm
Max. Operating temperature		**80**	°C
Weight		**66**	g
IP-protection		**-**	
Standards		**EN 61238-1:2003**	
Color/ Material		**Tin plated aluminium/ Black PA66**	
Mounting/ Connection		**Screw M4**	




CE RoHS

Description

OTE-connectors are designed to be used connecting aluminium and cobber conductors to equipment.

Drawing



Package

Package	**Box**	pcs/ package	**30**	Weight [Kg]	**2,20**
Length [mm]	**300**	Width [mm]	**205**	Height [mm]	**100**